


DC REVERSIBLE GEARMOTOR

A - OUTPUT SHAFT DIAMETER & LENGTH PER CUSTOMER REQUIREMENTS

EXTERNAL CONTROL: B=4.1, C=1.44

INTEGRAL CONTROL: B=5.1, C=1.65

- **OUTPUT SPEEDS FROM 0.5-200 RPM**
- **OUTPUT TORQUE TO 250 IN. LB.**
- **CONTINUOUS DUTY**
- **12 OR 24 V.D.C.**



SPEED & DIRECTIONAL CONTROLS (OPTIONAL)

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005		DRAWN	RPH 8/8/17		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV	
MATERIAL		ENG APPR.			
FINISH		MFG APPR.		SCALE: 1:4 SHEET 1 OF 1	
DO NOT SCALE DRAWING		Q.A.			
		COMMENTS:			