



DC REVERSIBLE GEARMOTOR

A - OUTPUT SHAFT DIAMETER & LENGTH PER CUSTOMER REQUIREMENTS

EXTERNAL CONTROL: B = 3.4, C = 1.44

INTEGRAL CONTROL: B = 4.4, C = 1.42-1.65 (1.65 SHOWN)

- **OUTPUT SPEEDS FROM 3-200 RPM**
- **OUTPUT TORQUE TO 35 IN. LB.**
- **CONTINUOUS DUTY**
- **6-30 VDC**
- **RoHS MARKED**

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005		DRAWN	RPH 7/17/17		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV A MINIBOX	
MATERIAL		ENG APPR.			
FINISH		MFG APPR.		SHEET 1 OF 1	
DO NOT SCALE DRAWING		Q.A.			
		COMMENTS:			