



AC UNIDIRECTIONAL GEARMOTOR

- A - 1.5" TO 2.9" DEPENDING ON TORQUE AND RPM REQUIREMENTS
- B - OUTPUT SHAFT LENGTH & DIAMETER PER CUSTOMER REQUIREMENTS
- OUTPUT SPEEDS FROM 1 - 800 RPM
- OUTPUT TORQUE TO 100 IN. LB.
- 24/120/240 VAC
- 50/60 HZ
- CONTINUOUS OR INTERMITTANT DUTY
- SELF-RESETTING THERMAL PROTECTION
- U.L., C.S.A. & T.U.V. APPROVED
- 18 GAUGE LEADS

OPTIONS

- 2.5" DIA. PLASTIC COOLING FAN
- HEAVY DUTY NEEDLE BEARINGS
- FRICTION BRAKES
- TERMINALS
- ONE WAY CLUTCH
- ADJUSTABLE CAMS & LIMIT SWITCHES

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS	
DIMENSIONS ARE IN INCHES	DRAWN	RPH	12/6/17		TITLE: ASP
TOLERANCES: FRACTIONAL ±	CHECKED				
ANGULAR: MACH ± BEND ±	ENG APPR.				
TWO PLACE DECIMAL ± .02	MFG APPR.				
THREE PLACE DECIMAL ± .005	Q.A.				
INTERPRET GEOMETRIC TOLERANCING PER:	COMMENTS:			SIZE	
MATERIAL				DWG. NO.	
FINISH				REV	
DO NOT SCALE DRAWING				SCALE: 1:5	
				SHEET 1 OF 1	