



AC UNIDIRECTIONAL GEARMOTOR

- A - 1.5" TO 2.9" DEPENDING ON TORQUE AND RPM REQUIREMENTS
- B - OUTPUT SHAFT LENGTH & DIAMETER PER CUSTOMER REQUIREMENTS
- OUTPUT SPEEDS FROM 1 - 800 RPM
- OUTPUT TORQUE TO 100 IN. LB.
- 24/120/240 VAC
- 50/60 HZ
- CONTINUOUS OR INTERMITTANT DUTY
- SELF-RESETTING THERMAL PROTECTION
- U.L., C.S.A. & T.U.V. APPROVED
- 18 GAUGE LEADS

OPTIONS

- 2.5" DIA. PLASTIC COOLING FAN
- HEAVY DUTY NEEDLE BEARINGS
- FRICTION BRAKES
- TERMINALS
- ONE WAY CLUTCH
- ADJUSTABLE CAMS & LIMIT SWITCHES

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS		
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005		DRAWN	RPH 12/6/17			TITLE: ASPCM
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE	DWG. NO.	
MATERIAL		ENG APPR.		A		
FINISH		MFG APPR.				
DO NOT SCALE DRAWING		Q.A.		SCALE: 1:5		SHEET 1 OF 1
		COMMENTS:				