



AC UNIDIRECTIONAL GEARMOTOR

- **A - OUTPUT SHAFT DESIGN PER CUSTOMER REQUIREMENTS**
- **B - 5/8"-2" DEPENDING ON RPM AND TORQUE REQUIREMENTS**
- **OUTPUT SPEEDS FROM 2-500 RPM**
- **OUTPUT TORQUE TO 50 IN. LB.**
- **24/120/240 VAC, 50/60 HZ**
- **CONTINUOUS OR INTERMITTANT DUTY**
- **SELF-RESETTING THERMAL PROTECTION**
- **U.L. & C.S.A APPROVED, C.E. MARKED**
- **18 GAUGE LEADS**

OPTIONS

- **2.5" PLASTIC COOLING FAN**
- **HEAVY DUTY NEEDLE BEARINGS**
- **FRICTION BRAKES**
- **TERMINALS**
- **ONE WAY CLUTCH**

| | | | | | | | | | | | |
|---|------------|-----------|----------|--|--|--------|----------|-----|----------|------------|--|
| UNLESS OTHERWISE SPECIFIED: | | NAME | DATE | REX ENGINEERING | | | | | | | |
| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± | | DRAWN | RPH 4/18 | | | TITLE: | | | | | |
| INTERPRET GEOMETRIC TOLERANCING PER: | | CHECKED | | <table border="1"> <tr> <td>SIZE</td> <td>DWG. NO.</td> <td>REV</td> </tr> <tr> <td>A</td> <td>CMC</td> <td></td> </tr> </table> | | SIZE | DWG. NO. | REV | A | CMC | |
| SIZE | DWG. NO. | REV | | | | | | | | | |
| A | CMC | | | | | | | | | | |
| MATERIAL | | ENG APPR. | | | | | | | | | |
| FINISH | | MFG APPR. | | | | | | | | | |
| DO NOT SCALE DRAWING | | Q.A. | | SCALE: 2:3 | | | | | | | |
| | | COMMENTS: | | WEIGHT: | | | | | | | |
| | | | | SHEET 1 OF 1 | | | | | | | |