



4 BOSSES TAPPED 8-32,
10-32 OR ϕ .190
THROUGH HOLE

6 OPTIONAL
MOUNTING BOSSES

OPTIONAL
THROUGH SHAFT

OPTIONAL FAN
EXTENSION

WIRES EXIT
HERE

- OPTIONS:**
 TERMINALS
 SLIP CLUTCH
 FRICTION BRAKES
 PLASTIC COOLING FAN
 HEAVY DUTY NEEDLE BEARINGS
 ADJUSTABLE CAMS & LIMIT SWITCHES

AC UNIDIRECTIONAL GEARMOTOR

- A - OUTPUT SHAFT DETAILS PER
CUSTOMER REQUIREMENTS
 B - 5/8" - 2" DEPENDING UPON RPM &
TORQUE REQUIREMENTS

- OUTPUT SPEEDS FROM 1-800 RPM
- OUTPUT TORQUE TO 250 IN. LB.
- 24/120/240 VAC. 50/60 HZ
- CONTINUOUS OR INTERMITTANT DUTY
- SELF-RESETTING THERMAL PROTECTION
- U.L., C.S.A. RoHS & C.E. MARKED
- 18 GAUGE LEADS

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm ANGULAR: MACH \pm BEND \pm TWO PLACE DECIMAL \pm .02 THREE PLACE DECIMAL \pm .005		DRAWN	RPH 8/28/17		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE	
MATERIAL		ENG APPR.		DWG. NO.	
FINISH		MFG APPR.		REV	
DO NOT SCALE DRAWING		Q.A.		A	
		COMMENTS:		ESP-D	
				SCALE: 1:5	
				SHEET 1 OF 1	