



PLANETARY BRUSHLESS DC GEARMOTOR

- A - VARIES DEPENDING UPON GEAR RATIO, 4.92" SHOWN
- B - OUTPUT SHAFT DETAILS PER CUSTOMER REQUIREMENTS
- C - 1.7" TO- 3.1" DEPENDING ON RPM & TORQUE REQUIREMENTS, 2.1" IN CONFIG. SHOWN
- NEMA 23 MOUNTING INTERFACE
- ALL STEEL GEARING AVAILABLE
- OUTPUT SPEEDS FROM 1-800 RPM
- OUTPUT TORQUE UP TO 200 IN. LB. DEPENDING ON SPEED
- CONTINUOUS OR INTERMITTENT DUTY
- SELF-RESETTING THERMAL PROTECTION
- UL, CSA & TUV APPROVED
- 18 GAUGE LEADS

OPTIONS

- ϕ 2.5" COOLING FAN
- HEAVY DUTY NEEDLE BEARINGS
- FRICTION BRAKES
- TERMINALS

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL \pm ANGULAR: MACH \pm BEND \pm TWO PLACE DECIMAL \pm THREE PLACE DECIMAL \pm		DRAWN	RPH 5/23		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV	
MATERIAL		ENG APPR.			
FINISH		MFG APPR.		SCALE: 1:2 WEIGHT: SHEET 1 OF 1	
DO NOT SCALE DRAWING		Q.A.			
		COMMENTS:			