



**AC REVERSIBLE GEARMOTOR**

**A - OUTPUT SHAFT DESIGN PER CUSTOMER REQUIREMENTS**

**B - 5/8"-2" DEPENDING ON RPM & TORQUE REQUIREMENTS**

**OUTPUT SPEEDS FROM 1-800 RPM**

**OUTPUT TORQUE TO 100 IN. LB.**

**24/120/240 VAC, 50/60 HZ**

**CONTINUOUS OR INTERMITTANT DUTY SELF-RESETTING THERMAL PROTECTION**

**U.L. & C.S.A APPROVED, C.E. MARKED**

**3 WIRE, PERMANENT SPLIT CAPACITOR CONSTRUCTION**

**18 GAUGE LEADS, LENGTH AS REQUIRED**

**OPTIONS**

**HIGH TEMPERATURE PLASTIC FAN**

**HEAVY DUTY NEEDLE BEARINGS**

**ADJUSTABLE CAMS & LIMIT SWITCHES**

**CAPACITOR**

**FRICTION BRAKES**

**TERMINALS**

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>REX ENGINEERING</b>	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		DRAWN	RPH 4/18		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV	
MATERIAL		ENG APPR.			
FINISH		MFG APPR.		SCALE: 2:3 WEIGHT: SHEET 1 OF 1	
DO NOT SCALE DRAWING		Q.A.			
		COMMENTS:			