



AC REVERSIBLE GEARMOTOR

A - OUTPUT SHAFT DESIGN PER CUSTOMER REQUIREMENTS

**B - 6.20" FOR 240V
5.90" FOR 120 V**

SINGLE OUTPUT SPEEDS AVAILABLE FROM 3-500 RPM

**OUTPUT TORQUE TO 250 IN. LB.
CONTINUOUS DUTY WITH FAN**

120/240 VAC, 50/60 HZ

0.10 HP

ALL BALL BEARING & NEEDLE BEARING CONSTRUCTION

OPTIONS

3.5" DIAMETER COOLING FAN

NOTE: A CAPACITOR IS REQUIRED AND CAN BE FURNISHED LOOSE OR MOUNTED, WIRED & INSULATED

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING							
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		DRAWN	RPH 4/18			TITLE:					
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		<table border="1"> <tr> <td>SIZE</td> <td>DWG. NO.</td> <td>REV</td> </tr> <tr> <td>A</td> <td>B</td> <td></td> </tr> </table>		SIZE	DWG. NO.	REV	A	B	
SIZE	DWG. NO.	REV									
A	B										
MATERIAL		ENG APPR.									
FINISH		MFG APPR.									
DO NOT SCALE DRAWING		Q.A.		SCALE: 2:3							
		COMMENTS:		WEIGHT:							
				SHEET 1 OF 1							