



**AC UNIDIRECTIONAL GEARMOTOR**

- A - OUTPUT SHAFT DESIGN PER CUSTOMER REQUIREMENTS
- B - 5/8"-2" DEPENDING ON RPM AND TORQUE REQUIREMENTS
- OUTPUT SPEEDS FROM 2-500 RPM
- OUTPUT TORQUE TO 50 IN. LB.
- 24/120/240 VAC, 50/60 HZ
- CONTINUOUS OR INTERMITTANT DUTY
- SELF-RESETTING THERMAL PROTECTION
- U.L. & C.S.A APPROVED, C.E. MARKED
- 18 GAUGE LEADS
- 3 WIRE, PERMANENT SPLIT CAPACITOR CONSTRUCTION

**OPTIONS**

- 2.5" PLASTIC COOLING FAN
- HEAVY DUTY NEEDLE BEARINGS
- FRICTION BRAKES
- TERMINALS
- CAPACITOR

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>REX ENGINEERING</b>	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ±		DRAWN	RPH 4/18		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV	
MATERIAL		ENG APPR.			
FINISH		MFG APPR.		SCALE: 2:3 WEIGHT: SHEET 1 OF 1	
DO NOT SCALE DRAWING		Q.A.			
		COMMENTS:			