



AC REVERSIBLE GEARMOTOR

A - OUTPUT SHAFT DESIGN PER CUSTOMER REQUIREMENTS

B - 5/8" - 2" DEPENDING ON RPM & TORQUE REQUIREMENTS

- OUTPUT SPEEDS FROM 0.3-500 RPM
- OUTPUT TORQUE TO 50 IN. LB.
- 24/120/240 VAC. 50/60 HZ
- CONTINUOUS OR INTERMITTANT DUTY
- SELF-RESETTING THERMAL PROTECTION
- U.L., C.S.A. RoHS & C.E. MARKED
- 18 GAUGE LEADS
- 3 WIRE, PERMANENT SPLIT CAPACITOR CONSTRUCTION

OPTIONS:

PLASTIC COOLING FAN

HEAVY DUTY NEEDLE BEARINGS

FRICION BRAKES

TERMINALS

ONE WAY CLUTCH

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS			
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005		DRAWN	RPH 8/28/17			TITLE:	
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV A HPSC			
MATERIAL		ENG APPR.				SCALE: 1:2	
FINISH		MFG APPR.				SHEET 1 OF 1	
DO NOT SCALE DRAWING		Q.A.					
		COMMENTS:					