



DC REVERSIBLE GEARMOTOR

**A - OUTPUT SHAFT DIAMETER & LENGTH
PER CUSTOMER REQUIREMENTS**

- OUTPUT SPEEDS FROM 2-500 RPM
- OUTPUT TORQUE TO 50 IN. LB.
- CONTINUOUS DUTY
- 6-30 V.D.C.

OPTIONS

- HEAVY-DUTY NEEDLE BEARINGS
- ELECTRONIC NOISE ATTENUATORS
- TORQUE-LIMITING SLIP-CLUTCH

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	REX ENGINEERING GEARMOTORS	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005		DRAWN	RPH	8/8/17	TITLE:
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED			
MATERIAL		ENG APPR.			
FINISH		MFG APPR.			
DO NOT SCALE DRAWING		Q.A.			
		COMMENTS:			
SIZE	DWG. NO.			REV	
A	CXA				
SCALE: 1:2				SHEET 1 OF 1	