



**DC REVERSIBLE GEARMOTOR**  
**A - OUTPUT SHAFT DIAMETER & LENGTH PER CUSTOMER REQUIREMENTS**

- OUTPUT SPEEDS FROM 2 - 5-- RPM
- OUTPUT TORQUE TO 50 IN. LB.
- CONTINUOUS DUTY
- 6 - 30 V.D.C.

**OPTIONS:**

- HEAVY DUTY NEEDLE BEARINGS
- ELECTRONIC NOISE ATTENUATORS
- TORQUE-LIMITING SLIP-CLUTCH

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<b>REX ENGINEERING GEARMOTORS</b>	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± .02 THREE PLACE DECIMAL ± .005		DRAWN	RPH 7/28/17		
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		SIZE DWG. NO. REV	
MATERIAL		ENG APPR.			
FINISH		MFG APPR.		SCALE: 1:2	
DO NOT SCALE DRAWING		Q.A.		SHEET 1 OF 1	
		COMMENTS:			